

REACTOR

DC Reactor


CE RoHS



● Specification

- Rating : DC 380/440V
- Dielectric withstand : AC 3000V / 1min
- Insulation resistance : 100 M Ω 이상, DC 500V / 100M Ω
- IP Class : IP20
- Sound level : Less than 65db
- Operating temp. : -20℃ ~ +40℃

● Circuit Diagram



● DC 380/440V (Impedance Voltage : 5.5Vac)

MODEL	용량(KW)	정격전류 (A)	Dimensions(mm)							TYPE	Weight (kg)
			W	D	H	W1	D1	øE	øF		
WYDCL4-0.75	0.75	1.7	80	120	97	57	74	5×12	M4	A	1.5
WYDCL4-1.5	1.5	3.4	80	120	97	57	74	5×12	M4		2.2
WYDCL4-2.2	2.2	7.5	89	120	105	64.2	87	5×12	M4		3.1
WYDCL4-3.7	3.7	10	89	120	105	64.2	87	5×12	M4		4.2
WYDCL4-5.5	5.5	15	99	135	115	72	92	6×12	M4		5.9
WYDCL4-7.5	7.5	20	111	150	121	76.5	97.5	5.5×10	M4		7.2
WYDCL4-11	11	30	120	157	130	84	99.5	5.5×10	7	B	9
WYDCL4-15	15	38	140	167	146	97.9	112	6×12	7		11
WYDCL4-18.5	18.5	50	140	167	146	97.9	112	6×12	7		13
WYDCL4-22	22	58	140	167	146	97.9	112	6×12	7		14
WYDCL4-30	30	67	161	172	166	114	120	6×13	7		18
WYDCL4-37	37	82	161	172	166	114	120	6×13	9		18
WYDCL4-45	45	100	184	190	188	133.8	127	7×19	9		19
WYDCL4-55	55	121	184	190	188	133.8	127	7×19	9		22
WYDCL4-75	75	167	184	190	188	133.8	127	7×19	9		25
WYDCL4-90	90	201	184	190	188	133.8	127	7×19	11		28
WYDCL4-110	110	245	184	190	188	133.8	127	7×19	11		32
WYDCL4-132	132	290	219	266	255	180	160	7×15	11		34
WYDCL4-160	160	357	219	266	255	180	160	7×15	11		40
WYDCL4-185	185	420	219	266	255	180	160	7×15	13		57
WYDCL4-220	220	500	243	296	283	180	195	9×19	13		68

● Dimension

