


단상 단권형으로 입력 AC380V, 440V, 출력 AC110V, 220V로 탭식으로 일반 전원용으로 제작되었으며 복권식에 비해 1, 2차 구분없이 한개의 권선에서 인출된 권선 방식으로 제작 되었습니다.

With a single phase, it has been manufactured for general electric source with AC380V, 440V of input voltage and AC110V, 220V of output by soldering type. It is produced by auto transformer type from one coil without classification of the primary and secondary.



• Circuit Diagram





● Specifications

Insulation Class B

MODEL NO.	TYPE	SPECIFICATIONS		VA	DIMENSIONS (mm)									WEIGHT (kg)
		PRI.(V)	SEC.(V)		W	H	D	a	b	c	d	(a.c)Ø1	Ø2	
WYAU-10DWO	WB	0-110-220-380-440 (0V : COMMON)		10	70	44	38	50	60	19	-	-	4 x 6	0.28
WYAU-20DWO				25	85	52	44	59	72	23	-	-	4.5 x 7	0.45
WYAU-50DWO				25	95	60	55	69	81	31	-	-	5 x 7	0.78
WYAU-75DWO	WO	0-110-220-380-420-440-460 (0V : COMMON)		40	78	69	83	42	57	46	63	M4	5 x 12	1.34
WYAU-100DWO				60	78	69	88	42	57	56	68	M4	5 x 12	1.79
WYAU-150DWO				80	88	78	103	46	64	58	80	M4	5 x 12	1.98
WYAU-200DWO				100	99	85	105	46	72	63	96	M4	6 x 12	2.58
WYAU-300DWO				150	99	86	116	54	72	70	94	M4	6 x 12	3.23

● Dimension

• WB Type



• WO Type

