


WB Type

WO Type

• Circuit Diagram





Specifications

Insulation Class B

MODEL NO.	TYPE	SPECIFICATIONS		VA	A	DIMENSIONS (mm)										WEIGHT (kg)
		PRI.(V)	SEC.(V)			W	H	D	a	b	c	d	(a.c)Ø1	Ø2		
• 26V SERIES (12V x 2)																
WYSH-2601	WB	0-110-220	0-12-22-24-26 (12V x 2)	3	0.1	62	36	35	43	52	16	-	-	3.5 x 5	0.185	
WYSH-2602				5	0.19	70	44	38	50	60	19	-	-	4 x 6	0.28	
WYSH-2603				10	0.3	85	52	44	59	72	23	-	-	4.5 x 7	0.41	
WYSH-261				25	1	95	60	55	69	81	31	-	-	5 x 7	0.78	
WYSH-262				40	1.53	106	69	69	78	91	33	-	-	4.5 x 6.5	1.30	
WYSH-263	WO			80	3	88	78	103	46	64	58	80	Ø3.6	5 x 12	1.98	
• 30V SERIES (15V x 2)																
WYSH-3001	WB	0-110-220	0-15-24-27-30 (15V x 2)	3	0.1	62	36	35	43	52	16	-	-	3.5 x 5	0.185	
WYSH-3002				5	0.16	70	44	38	50	60	19	-	-	4 x 6	0.28	
WYSH-3003				10	0.3	85	52	44	59	72	23	-	-	4.5 x 7	0.41	
WYSH-3005				25	0.83	95	60	55	69	81	31	-	-	5 x 7	0.78	
WYSH-301				40	1.33	106	69	69	78	91	33	-	-	4.5 x 6.5	1.30	
WYSH-302	WO			80	2.66	88	78	103	46	64	58	80	Ø3.6	5 x 12	1.98	
WYSH-303				100	3.33	99	85	105	46	64	63	85	Ø3.6	5 x 12	2.78	
WYSH-305				150	5	99	86	116	54	72	70	94	Ø3.6	5 x 12	3.23	
• 38V SERIES (19V x 2)																
WYSH-3801	WB	0-110-220	0-19-32-35-38 (19V x 2)	3	0.1	62	36	35	43	52	16	-	-	3.5 x 5	0.185	
WYSH-3802				5	0.13	70	44	38	50	60	19	-	-	4 x 6	0.28	
WYSH-3803				10	0.3	85	52	44	59	72	23	-	-	4.5 x 7	0.41	
WYSH-3805				25	0.65	95	60	55	69	81	31	-	-	5 x 7	0.78	
WYSH-381				40	1.05	106	69	69	78	91	33	-	-	4.5 x 6.5	1.30	
• 50V SERIES (25V x 2)																
WYSH-5001	WB	0-110-220	0-25-40-45-50 (25V x 2)	5	0.1	70	44	38	50	60	19	-	-	4 x 6	0.28	
WYSH-5002				10	0.2	85	52	44	59	72	23	-	-	4.5 x 7	0.41	
WYSH-5005				25	0.5	95	60	55	69	81	31	-	-	5 x 7	0.78	
WYSH-5008				40	0.8	106	69	69	78	91	33	-	-	4.5 x 6.5	1.30	
WYSH-501	WO			80	1.6	88	78	103	46	64	58	80	Ø3.6	5 x 12	1.98	
WYSH-502				100	2	99	85	105	46	64	63	85	Ø3.6	5 x 12	2.78	

Dimension

• WB Type



• WO Type

