



● Features


- Wide Band : High Attenuation
- Band Width : 150KHz ~ 30MHz
- RoHS Compliant
- Inverter Output Type : Model Type"C"
(WYNFTH40T2C)

● Specifications


MODEL ITEM	SYMBOL	WYNFTH40T2A WYNFTH40T2C	WYNFTH50T2A WYNFTH50T2C	WYNFTH60T2A WYNFTH60T2C	WYNFTH80T2A WYNFTH80T2C	WYNFTH100T2A WYNFTH100T2C	WYNFTH120T2A WYNFTH120T2C	WYNFTH150T2A WYNFTH150T2C	WYNFTH200T2A WYNFTH200T2C	WYNFTH250T2A WYNFTH250T2C
Rated Voltage	V	500Vac								
Rated Current	A	40A	50A	60A	80A	100A	120A	150A	200A	250A
Frequency	Hz	50 / 60								
Dielectric Withstand	V	2500VAC for 1 minute (Line－Case)								
Insulation Resistance	M Ω	DC 100M Ω at the 500Vdc								
Leakage Current	mA	$\leq$ 5mA at the 500Vac					$\leq$ 26mA at the 500Vac			
Operating Temperature	℃	－25℃ ～ +100℃ [Refer to Derating Curve TYPE－2]								
Operating Humidity	RH	35 ～ 85%RH								
Weight	kg	1.2		2.2			2.7			

※ Derating Curve of page 519

● Circuit Diagram




● Terminal



Max 16, Min 6 (40~50A)
Max 23, Min 8 (60~100A)
Max 28, Min 8 (120~250A)

● Dimension



MODEL	W	H	D	a	b	c	d	M	Ø
WYNFTH40 ~ 50T2A	91	57.2	184	173.5	74	17	42.3	6	5
WYNFTH60 ~ 100T2A	115	75	235.2	218	96	24	58	8	5
WYNFTH120 ~ 250T2A	157.2	100.1	347.5	316	130	28.5	68.6	8	6.5

● Characteristics

