

SOLID STATE RELAY(SSR)

3Ø WY3G AC220V 10A~80A (DC/AC, AC/AC Type)



Metal
Bonding
Process



● 일반형(General Type)


삼상 일반형으로 제작된 제품으로 고신뢰성 부품을 선정하여 전기적 내환경을 강화한 제품으로 AC90~240V, 10~80A의 용량을 가지고 있으며 입력측에 LED 표시장치가 있는 일반형 SSR입니다.

• cUL 규격인증품 : . UL508 • UL Cer. No : E142643


This is a 3-phase general type product. This product featuring electric and environmental resistance reinforced by using highly reliable parts carries a capacity of AC90~220V, 10-80A It is an general type SSR is equipped with LED according to input control.

• cUL Std. No : . UL508 • UL Cer. No : E142643

● Dimension



● Terminal




Input Ter : Max 6.2, Min 3
Output Ter : Max 12, Min 4

● Specifications

※ cUL Certificated

ITEM		MODEL	※WY3G3C10/20/30/40Z4 WY3G3C50/60/80Z4				WY3G3C10/20/30/40Z40 WY3G3C50/60/80Z40	
			WY3G3C10/20/30/40R4 WY3G3C50/60/80R4				WY3G3C10/20/30/40R40 WY3G3C50/60/80R40	
O U T P U T	Rated voltage	220VAC						
	Voltage range	90 ~ 240VAC						
	Non repetitive peak voltage	600V						
	Rated load current	15A	20A	30A	40A	50A	60A	80A
	Frequency	50 / 60Hz						
	Peak surge current	160A	260A	420A	420A	480A	480A	480A
	leakage current	10mA						
	Contact voltage drop	1.7V	1.8V	1.8V	1.8V	2.0V	2.0V	2.0V
Minimum operating current		1.0A						
I N P U T	Maximum input voltage	32VDC				240VAC		
	Input voltage range	4 ~ 32VDC				90 ~ 240VAC		
	Input current	10mA				16mA(MAX)		
	Minimum operating voltage	3.0VDC				85VAC		
	Turn off voltage	1.4VDC				20VAC		
G E N E R A L	Dielectric withstand	2000VAC / rms / 1Min						
	Insulation resistance	DC 500V / 100M Ω						
	Response time	R4 : 1 $\pm$ 1ms Z4 : 8.3 $\pm$ 1ms R40, Z40 : 30 $\pm$ 1ms						
	Circuit control	Z40, Z4 : Zero cross type R40, R4 : Random cross type						
	Operating temperature	-10 ~ +60°C						
	Storage temperature	-20 ~ +80°C						
	Weight	0.4kg						

● Block Diagram



* 3PH ZVC : 3PH ZERO CROSS VOLTAGE CIRCUIT
* 3PH RVC : 3PH RANDOM CROSS VOLTAGE CIRCUIT

● Application Circuit

